

COLORdash Batten-Quad 6



SPECIFICATIONS

Optical

- Light Source: 6 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy
- Color Temperature (range): 2,800 to 10,000 K
- Installed Optics: 20°
- Beam Angle: 17°
- Field Angle: 33°
- Illuminance (total): 390.7 lux @ 5 m
- PWM Frequency: 600 Hz

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Built-in Automated Programs: Yes

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Neutrik powerCON cables
- 3- or 5-pin DMX Cables

FEATURES

- Metal construction for added durability
- Individual pixel control
- Silent flicker-free operation
- Simple and complex DMX channel profiles for programming versatility
- Mount multiple units in stack or end-to-end to maintain pixel pitch

Construction / Physical

- Dimensions: 22 x 2.6 x 6.5 in (560 x 65 x 164 mm)
- Weight: 5 lb (2.3 kg)
- Exterior Color: Black

Connections

- Power Connection: Edison plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX
- DMX Channels: 4, 6, 10, 24 or 28
- Modes/Personalities: 5 personalities (4, 6, 10, 24, 28)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 17 units @ 120 V; 30 units @ 208 V; 33 units @ 230 V
- Power and Current: 90 W, 0.76 A @ 120 V, 60 Hz

- Power and Current: 94 W, 0.45 A @ 208 V, 50 Hz
- Power and Current: 96 W, 0.41 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET
- IP Rating: IP20, dry location

What's Included

- COLORdash Batten-Quad 6
- Neutrik powerCON power cord
- 2 Trunnions