

# HOTSTIK



## COB II

### 12x 25W COB LED Wash Fixture

#### Color Rich

Strong and powerful, HotStik™ 5 COB II fixtures deliver intensely bright, super rich colors from its 1-meter long LED batten-style housing. Powered by 12x 25-watt high output 5-in-1 RGBAW COB LEDs, it maintains all the same great features that made the original HotStik™ 5 COB such an outstanding success! Its 5-in-1 RGBAW LEDs provide a vastly increased color gamut and drastically reduced multicolored shadowing versus conventional LEDs

#### Ergonomically Designed

Programming is a snap with the HotStik™ 5 COB II's large LED control panel. The 1- meter linear wash fixture is well constructed with powerCON® compatible power in/out connectors and 3-pin DMX connectors for easy daisy-chaining of DMX and power. With an awesome array of built-in color macros, automated programs, plus sound active mode via master/slave, the HotStik™ 5 COB II is a perfect solution for any type of accent lighting.

Luminous Intensity:

Lux/m	Red	Green	Blue	Amber	White	All
1m	3,130	3,550	3,910	1,330	4,690	15,660
2m	1,120	1,320	1,360	510	1,560	5,700
3m	520	580	620	250	720	2,600
4m	300	340	350	150	410	1,420
5m	210	230	240	100	280	1,000



#### Main Features

- 12x 25W 5-in-1 COB LEDs, 100,000 hours
- Variable electronic strobe
- Variable electronic dimmer
- Built-in color & chase macros via DMX
- Built-in autoprograms + Sound Active via M/S
- RGBAW color mixing ability in standalone mode
- Beam Angle: 60 degree
- 3-pin male input and 3-pin female output
- User selectable 4/5/9 or 10-Channel DMX modes
- Directly power wiCICLE® wireless via DMX
- Flicker-free constant-current LED driver
- Easy to use LED control panel
- powerCON® compatible AC power In/Out connectors



#### Optical

Light source: 12x 25W  
5-in-1 COB LEDs, 100,000  
hours

Beam Angle:  
60 degree



#### Weight + Dimensions

38.82" (986 mm) x 3.4"  
(85 mm) x 9.3" (235  
mm)

Weight:  
23.2 lbs (10.5 kg)



#### Control

DMX Channels: 4/5/9 or  
10-Channels

Input: 3-pin XLR Male

Output: 3-pin XLR  
Female

Operating Modes:  
Standalone, Master/Slave,  
Sound Active, Color  
Preset



#### Power + Current

Operating Voltage:  
100-264VAC, 50-60Hz

Fuse: 3.5A 250V

Power Consumption:  
290W, 3.66A, PF: .65



#### Warranty + Certifications

2-year limited warranty,  
does not cover  
malfunction  
caused by damage to  
LEDs