



12* 15W 4-in-1 LED IP65 Rated PAR w/Zoom

Rocking someone like a hurricane? Been thunderstruck? Making it rain men? No matter what kind of tempest you bring to the stage you need the TOURnado™ WIMAX Series from Blizzard Lighting.

The TOURnado™ WIMAX QZoom brings more lightning for your thunder with higher output than ever before. Get super bright RGBW color mixing from 12x 15W 4-in-1 LEDs with 8°-50° zoom.

The TOURnado™ WIMAX QZoom weathers almost any storm. It's IP65 outdoor rated and sports a larger natural convection cooled cast aluminum housing than previous models. It has a tempered glass lens and watertight internal gaskets. The back has outdoor rated 3-pin XLR data and AC power input/output connectors with rubber seals.

It's time to truly unleash the storm and go wireless. The built-in W-DMX™ receiver works seamlessly with any W-DMX™ product and provides ultra-stable wireless communication for more than 500 meters (line-of-sight)!

All TOURnado™ WIMAX fixtures have a 4-button control panel with an OLED display. You have total control including master/slave settings, 5 auto modes, custom programs (up to 3* 20 scene programs), fade, strobe, manual color adjustments, multiple user-selectable 32-bit dimming modes and more.

Riders on the storm, time to mount up and experience the TOURnado™ WIMAX QZoom.



IP65

SUITABLE FOR OUTDOOR USE

Main Features

- Color mixing via 12x 15W RGBW 4-in-1 LEDs
- IP65 rated outdoor LED fixture
- OLED control menu with 4x touch sensitive buttons
- 8°-50° zoomable beam angle
- Built-in wireless W-DMX™ receiver
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Color mixing ability in standalone mode
- 5/7/11-channel DMX profiles w/32-bit dimming
- Convection cooled cast aluminum housing
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current LED driver
- IP rated locking power and 3-pin DMX connections
- Dimensions: 13.8x6.5x11.1 inches (351x156x281 mm)
- Weight: 17.0 lbs (7.8 kg)



Optical

Light Source: 12* high output 15-watt RGBW LEDs

8°-50° zoomable beam

Flicker-free LEDs

Luminous Intensity:
(8°) 15,243 Lux @ 3M,
5,400 Lux @ 5M,
(50°) 1,100 Lux @ 3M,
424 Lux @ 5M



Wireless Receiver

Transmission band:
2.4Ghz ISM (2.4-2.525Ghz)

Channels: 512

Receiver sensitivity:
-94dBm



Control

Protocol: USITT DMX-512

5/7/11-channel DMX modes

Standalone, master/slave, DMX modes

IP65 Seetronic 3-pin DMX input/output

4-button OLED control menu display



Power + Current

100-264VAC, 47-63 Hz

Power Consumption:
180W



Warranty + Certifications

2-year limited warranty, does not cover malfunction caused by damage to LEDs

cETLus certified



blizzardlighting.com

info@blizzardlighting.com

[1.866.493.5025](tel:1.866.493.5025)

[1.866.493.6025](tel:1.866.493.6025)