

WELL Pad



SPECIFICATIONS

Optical

- Light Source: 96 LEDs (24 red, 24 green, 24 blue, 24 amber) 1 to 3 W, (500 mA), 50,000 hours life expectancy
- Beam Angle (w/o filter): 22°
- Beam Angle (w/filter): 27°
- Field Angle (w/o filter): 38°
- Field Angle (w/filter): 51°
- Illuminance (w/o filter): 553 lux @ 5 m
- Illuminance (w/filter): 316 lux @ 5 m

Dynamic Effects

- Tilt: 90°
- Tilt Ranges: 0° to 90° tilt
- Color Macros: 5 macros
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07

FEATURES

- A completely wireless, IP65 rated, battery powered up-light with 96 single color (red, green, blue, and amber) LEDs that is controlled by W-DMX or IR remote
- Drop in case for easy storage and recharging of the battery
- Magnetic diffuser filter included
- 9 hours of operation at full output with a recharge time of 6 hours
- Built in automated programs recallable by IR, W-DMX or manually
- 90-degree rotation of the panel from the base for easy direction of light
- M12 threaded insert for easy clamp installation and a Kensington lock position for securing your investment
- IP65 rating for temporary outdoor usage

Construction / Physical

- Dimensions: 15.98 x 8.38 x 3.99 in (406 x 213 x 101.5 mm)
- Dimensions (charging case): 26.29 x 22.83 x 19 in (668 x 580 x 482.6 mm)
- Weight (single unit): 21.6 lb (9.8kg)
- Weight (charging case): 67.8 lb (30.8kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON (ROAD CASE ONLY)
- Power Input: Neutrik powerCON
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: W-DMX
- DMX Channels: 4, 6 or 10
- Modes/Personalities: 3 personalities (4Ch, 6Ch, 10Ch)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current (single unit charging): 120 W, 0.996 A @ 120 V, 60 Hz
- Power and Current (charging case): 480 W, 3.984 A @ 120 V, 60 Hz
- Power and Current (single unit charging): 135 W, 0.654 A @ 208 V, 60 Hz
- Power and Current (charging case): 540 W, 2.616 A @ 208 V, 60 Hz
- Power and Current (single unit charging): 137 W, 0.594 A @ 230 V, 50 Hz
- Power and Current (charging case): 548 W, 2.376 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE
- IP Rating: IP65, temporary outdoor/wet use with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- WELL Pad X4
- Charging case
- IR remote
- (4) Diffusion filters
- powerCON power cable with Edison plug