

SL PUNCHLITE 220

Date: _____

Type: _____

Firm Name: _____

Project: _____

The innovative and large motorized zoom range of 8-40° delivers flexibility to your lighting design. The honeycomb lens design maximizes the light emitting surface and delivers a powerful blended output. The effective passive cooling design delivers uncompromised saturated color performance. Ideal to highlight performers, objects or building elements with a narrow shaft of light, or flood a wide area with a powerful wash of color.



- Double yoke for floor standing or hanging.
- Silent passive cooling.
- Harmonize color calibration.

- Outdoor rated (IP65) power and DMX connections - Rated against water spray from any direction, providing weather protection.

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/sl-punchlite-220>



VARI***LITE**

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Source

| | |
|------------------------------|--|
| LED | 18 x Quad chip RGBW or RGBA |
| Source Max Power Consumption | 18 x 10 W |
| Dimming | Electronic 8-bit / 16-bit |
| Dimmer Curves | Square Law (Default), Linear, S -Curve |
| Strobe Speed | 0 - 30Hz |
| Strobe Modes | Continuous, Random, Random Sync |

Optical Performance

| | |
|--|---|
| Lens Size | 212 mm (8.3 in) |
| Zoom Range | 8 - 40° |
| Zoom Control | Motorized 8-Bit |
| Output Lumens | 3500 |
| Default Color Output Color Temperature | 6500 K (RGBW Version White Only LED Only) |
| CRI RA | > 90 |

Color System

| | |
|------------------------|----------------------------------|
| Additive Color Mixing | RGBW |
| Color Mixing Control | RGBW 8-bit, RGBW 16-bit, HSIC |
| Color Calibration | Selectable On/Off |
| Preset CTT Levels (10) | 2700 to 10,000k |
| Color Presets | 32 Calibrated Colors (RGBW Only) |
| Color Wheel Effects | Color Preset Chase |

Electrical

| | |
|------------------|---|
| Max output Power | 230 W |
| Consumption | |
| Power Connection | Captive True1 compatible In/Thru cables, IP65, 490mm (19.3 in) True1 compatible input connector included |
| Input Voltage | 100–240 VAC, 50 / 60 Hz |

Data

| | |
|---------------------|---|
| Supported Protocols | DMX-512A (RDM) |
| DMX Modes | |
| 16-Bit | 18 / 34 Channels |
| 8-Bit | 11 / 19 / 21 Channels |
| HSIC | 11 / 21 Channels |
| Simple 8-Bit | 8 / 16 Channels |
| Data Connections | Captive 5-Pin XLR In/thru cables, IP65, 490mm (19.3 in) |
| Zone Control | 1 / 3 Pixels |
| Manual Mode | On Board local Control |

Noise Level / Fan Control

| | |
|---------------------|------------|
| Cooling System Type | Convection |
|---------------------|------------|


Mounting

| | |
|--------------------------------------|---|
| Yoke / Feet Type | Double clutch locking yoke >270° Swivel Yoke M12 (1/2") Centre hole |
| Fixture mounting/Hanging orientation | Hanging - Floor - Side |
| Secondary Safety Wire Point | 1 x Safety point located on body of fixture Safety Wire not included |

Photometrics and IES Files

For IES files and photometric reports, please refer to the product page:
<https://www.vari-lite.com/global/products/sl-punchlite-220>

Dimensions



Physical

| | |
|-----------------------|---|
| Construction | Superstructure made of Aluminum, and steel metal plates, Covers Aluminum |
| IP Rating | IP65 |
| Standard Finish | Black |
| Dimensions | 254 x 320 x 252 mm (10.0 x 13.0 x 10.0 in) |
| Fixture Weight | 10.0 kg (23.0 lb) |
| Operating Temperature | -10-45°C (14-113°F) |

Certification and Safety

| | |
|--------------|-----------------|
| Approbations | CE, C-Tick/cETL |
|--------------|-----------------|

Luminaire and Accessories

| Product type | Order Code |
|---|-----------------|
| SL PUNCHLITE 220, RGBA | SLPUNCHLITE220A |
| SL PUNCHLITE 220, RGBW | SLPUNCHLITE220 |
| Accessories | |
| Accessory Holder | 89-020-6090-00 |
| SL PUNCHLITE 220, Accessory Holder, Black | |
| Top hat | 28-002-1450-00 |
| SL PUNCHLITE 220, Top hat, Black | |



© 2023 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

05/08/2023

Vari-Lite
<https://www.vari-lite.com/global/products/sl-punchlite-220>