

Beam/Wash Moving Head with Zoom + Glo™

Stiletto™ Glo19 is a powerful beam/wash luminaire that is built to impress with its sharp beams and glowing personality!

They feature 19x 15-watt OSRAM™ RGBW LEDs, a 11-58° zoomable beam angle, and also an additional controllable RGB LED array for backlight “Glo” eye-candy effects which can create a multi-layered dynamic effect that will ‘wow’ any crowd.

Users have multiple DMX control modes at their disposal including full 93-channel mode which gives users access all of its fantastic features including smooth dimming, pan, tilt, fine pan/tilt, individual LED RGBW intensity, “Glo” background control, patterns, zoom, plus multiple strobe effects. Structurally unique from its other 5 channel modes, Stiletto™ Glo19 fixtures also offer a 14-channel “Classic Mode”, which is specifically designed to be compatible with other comparable fixtures found on the market today.

Stiletto™ Glo19 fixtures have impressive speed and accuracy due to their 3-phase stepper motors, and they have a 5-button full-color graphical LCD control panel for easy programming. Plus, they also feature internal 2-setting fan cooling (auto/high), so when your shows get hot, your fixtures won’t!

They also come equipped with an industry standard PowerCON® compatible power Input, 3-pin and 5-pin DMX In/Out jacks, and dual quarter-turn “Omega” quick connect type clamp brackets for secure mounting.

Make your light shows epic with Stiletto™ Glo19 fixtures!

Main Features

- 19*15W OSRAM™ 4-in-1 RGBW LEDs (beam/patterns)
- RGB color mixing Glo™ control (background LED array)
- Independent control of beam and background illumination
- Motorized zoom: 11°-58°
- 4x user selectable dimming curves
- Linear smooth dimming 0-100%
- 1000-2500K CTC (Color Temperature Control)
- 540° pan & 270° tilt (16-bit)
- Internal fan cooling system
- Color macro effects
- USITT DMX-512 (14/17/28/74/85 and 93-channel)
- 3/5-pin XLR input and output
- 5-button menu with LCD display

STILETTO
Glo 19™



Power

- Operating Voltage: 110-220VAC, 50-60Hz
- Power Consumption: 118W, .76A, PF: .99

Light Source

- LED 19*15W OSRAM™ 4-in-1 RGBW LEDs (patterns) + RGB color mixing secondary background LED array

Optical

- Beam Angle: 11°-58° zoomable beam angle
- Luminous Intensity: Narrow: 31,311 Lux @2M | 5,058 Lux @ 5M | Wide: 2,148 Lux @ 2M | 363 Lux @ 5M

Control

- Protocol: USITT DMX-512
- DMX Channels: 14/17/28/74/85 and 93-Channel
- 3/5-pin XLR Input/Output
- Standalone, Master/Slave

Weight & Dimensions

- Width: 12.5" x 8" x 14.5" (318.4 x 203.6 x 369.3 mm)
- Weight: 17.5 lbs (8 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.