

VL800 PROPAR

Date: _____

Type: _____

Firm Name: _____

Project: _____


The Vari-Lite VL800 PROPAR is an advanced LED event PAR fixture that has the DNA of Vari-Lite built in. This high output fixture includes a quiet running motorized zoom and is a cost-effective solution that looks and feels like the professional luminaire you'd expect from Vari-Lite. The VL800 PROPAR offers full RGBW color mixing and has gel-matched color presets to deliver the same visual results customers are accustomed to using, as well as multi-mode fan control for use in quiet environments.



- Cost-effective, high output LED professional PAR built by Vari-Lite - affordable LED PAR from a brand you trust.
- Full RGBW color mixing - variable color mixing with saturation control, offering numerous vivid and creative color options.
- Gel color presets matched to traditional gel numbers - use the colors you have always used without the need to change gels.
- Motorized zoom - remote beam angle control with the smooth zoom movement of a Vari-Lite fixture.

- Multi-mode fan control - adjust settings to control fan noise. Offers a low dB experience across all frequencies, eliminating buzzing or hums from an otherwise quiet device. Mode options include standard, studio, and whisper mode.
- Adjustable frequency to exceed camera frame rates - camera-friendly fixtures for IMAG or live televised events.

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/vl800-propar>



VARI*LITE

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Source

LED	7 x Quad chip RGBW
Source Max Power Consumption	7 x 30 W
LED Refresh Rate	1200Hz to 25kHz
Dimming	Electronic 8-bit / 16-bit
Dimmer Curves	Square Law (Default), Linear, S -Curve
Dimmer Control Option	Dimmer Snap On/Off On reduces auto dimmer smoothing
Strobe Speed	0 - 30Hz
Strobe Modes	Continuous, Random, Random Sync

Optical Performance

Lens Size	137 mm (5.4 in)
Zoom Range	6 - 40°
Field Angle	10 - 30°
Zoom Control	Motorized 8-Bit
Output Lumens	Standard - 3,500 Studio - 2,800 Whisper - 2,500
Output CCT	6500 K (White LED Only)
CRI RA	> 90
Tm30	Rf 60 / Rg 123

Color System

Additive Color Mixing	RGBW
Color Mixing Control	RGBW 8-bit, RGBW 16-bit
Color Calibration	Selectable On/Off
Color Mixing Control Option	Color Snap On/Off On reduces auto smoothing color to create faster color changes
Preset CTT Levels (10)	2700 - 10000 K
Color Presets	32 Calibrated Colors
Color Preset Effects	Color Preset Chase

Electrical

Max output Power Consumption	230 W
Power Connection	TrueOne Compatible - In / Thru Power cable not included - input connector only
Input Voltage	100–240 VAC, 50 / 60 Hz

Data

Supported Protocols	DMX512-A (RDM)
DMX Modes	
16-Bit	15 Channels
8-Bit	10 Channels
Color Mode 8-Bit	4 Channels
Data Connections	5 - Pin XLR Input and Thru
Manual Preset Mode	Advanced Feature local control

Noise Level / Fan Control (Base Level 18.6 dB)

Standard Mode	33.5 dB
Standby Mode	20.1 dB
Fan Mode	Continuous (On) / Auto Ramping
Fan Level Preset	Standard, Studio, Whisper
Cooling System Type	Hybrid sealed liquid and forced air system

Mounting


Yoke / Feet Type	270° Swivel Yoke M12 (1/2") Centre hole or 107mm Omega Bracket - Integrated kickstand
Fixture mounting/Hanging orientation	Hanging - Floor - Side *See user manual for side hang guidance and restrictions
Secondary Safety Wire Point	1 x Safety point located on rear of fixture housing Safety Wire not included

Photometrics and IES Files

Narrow @ 5 m / 16.4 ft	6,700 lux (622 fc)
Wide @ 5 m / 16.4 ft	390 lux (36 fc)
Narrow @ 10 m / 32.8 ft	1,645 lux (153 fc)
Wide @ 10 m / 32.8 ft	120 lux (11 fc)

For IES files and photometric reports, please refer to the product page:
<https://www.vari-lite.com/global/products/vl800-propar>

Dimensions



Physical

Construction	Superstructure made of Aluminum, and steel metal plates, Covers self-extinguishing fire retardant ABS PC (V0 class)
IP Rating	IP20
Standard Finish	Black, White
Dimensions	228 x 181 x 304 mm (9.0 x 7.0 x 12.0 in)
Packed Dimensions	550 x 365 x 305 mm (12.0 x 9.0 x 7.0 in)
Fixture Weight	6.0 kg (13.0 lb)
Packed Weight	8.0 kg (17.0 lb)
Operating Temperature	0-40°C (32-104°F)

Certification and Safety

Approbations	CE, ETL, UL, FCC CSA, RoHS, ISO 9001
--------------	--------------------------------------

Luminaire and Accessories

Product type	Order Code
VL800 PROPAR, Black	912400575000
VL800 PROPAR, White	912400576843
Accessories	
BARNDOOR Black	912400575016
VL800 PROPAR, Barndoor - 4 Leaf , Black	
BARNDOOR White	912400576947
VL800 PROPAR, Barndoor - 4 Leaf , White Outer	
Top hat black	912400575017
VL800 PROPAR, Top hat, Black	
Top hat white	912400576948
VL800 PROPAR, Top hat, White Outer	
Omega bracket	3002000390
VL & 107mm 1/2 turn omega Bracket x 1 (VL800 PROPAR,EVENTPAR,EVENTWASH, CODA and AURORA)	



© 2023 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

05/08/2023

Vari-Lite
<https://www.vari-lite.com/global/products/M800-propar>