

Maverick MK3 Profile



SPECIFICATIONS

Optical

- Light Source: 1 LEDs (CW) 820 W, (24 A), 7,258 K, 50,000 hours life expectancy
- Color Temperature (at full): 7,441 K
- Front lens diameter: 147 mm
- CRI: 74.1
- CRI W / Filter: 91.2
- TLCI: 50.9
- Beam Angle: 5.9° to 52.7°
- Field Angle: 7.6° to 61.4°
- Zoom Range: 5.9° to 64.1°
- Cutoff Angle: 8.1° to 64.1°
- Lumens – Source: 51,000
- Lumens – Output: 23,000
- Illuminance (5.9°): 58,869 lux @ 5 m
- Illuminance (52.7°): 1,860 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 6000 Hz, 15000 Hz

Dynamic Effects

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 6 + white, split colors, continuous scroll at variable speeds
- Colors: CMY flags, CTO flag, CRI filter, color correction
- Gobos (1): 7 + open (7 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobos (2): 9 + open (9 glass), continuous scroll at variable speeds
- Effect Wheel: 1 effect
- Framing Shutters: Yes
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Focus: Motorized
- Frost 1: Light Frost - Motorized
- Frost 2: Medium Frost - Motorized
- Iris: Motorized
- Prism: 5 linear facets, motorized, rotating
- Prism: 5 Circular facets, motorized, rotating
- Strobe Rate: 0 to 25 Hz
- Move-in-Black: Yes
- Dim Curves: 5

FEATURES

- Fully featured 820 W LED yoke profile fixture including CMY+CTO color mixing, a four blade framing shutter system with rotation, a color wheel, a CRI filter, animation wheel, a 9:1 zoom, two independently layerable prisms, two frosts, a static and a rotating gobo wheel
- 16-bit dimming of master dimmer for smooth control of fades
- Variable CMY + CTO color mixing system to create a wide pallet of colors
- Independently layerable 5 facet linear and 5 facet round prisms for increased prism options
- One rotating and one static gobo wheel for dynamic texture possibilities
- Independent light and medium frosts for beam control
- + or - 60 degree rotation framing shutter system to allow for better framing positioning.
- Animation wheel for enhanced visual effects
- Iris for total beam control
- RDM control over DMX for fixture reporting
- 5.9° to 64.1° zoom range for variable beam sizes
- 3 menu presets and preset cross load for decreased shop setup time
- True 1 compatible power input
- Battery backup display with auto-rotate depending on fixture orientation

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- IP Rated Seetronic® Powerkon Extensions
- DMX cables
- Flight Case: TBA
- Upload 08 software uploader

Construction / Physical

- Dimensions: 16.10 x 12.20 x 29.43 in (409 x 310 x 748 mm)
- Weight: 76.4 lb (34.7 kg)
- Exterior Color: Black
- Housing Material: High-impact flame-retardant polymer

Connections

- Power Connection: Edison plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65

- Data Connectors: 3- and 5-pin XLR, Amphenol XLR Net RJ45 connectors in/out
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: Art-Net, DMX, W-DMX, sACN, RDM
- DMX Channels: 38 or 54
- Art-Net Channels: 38 or 54
- Modes/Personalities: 2 personalities (38, 54)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 1,230 W, 10.34 A @ 120 V, 60 Hz
- Power and Current: 1,190 W, 5.81 A @ 208 V, 60 Hz
- Power and Current: 1,180 W, 5.24 A @ 230 V, 50 Hz
- Power and Current (resting): 120 W, .98 A @ 120 V, 60 Hz
- Power and Current (resting): 126 W, .60 A @ 208 V, 60 Hz
- Power and Current (resting): 127 W, .55 A @ 230 V, 50 Hz
- Breaker Size: F20 A, 250 V

Certifications / Qualifications

- CE, MET, FCC
- IP Rating: IP20, dry location
- Noise Level (ambient): 36.5 dB level @ 1 m
- Noise Level (Full): 62.1 dB level @ 1 m
- Noise Level (Eco): 43 dB level @ 1 m
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- Maverick MK3 Profile
- Seetronic Powerkon IP65 power cord
- 2 Omega brackets with mounting hardware
- Quick Reference Guide