

VL600 ACCLAIM PLE+

Date: _____

Type: _____

Firm Name: _____

Project: _____

The VL600 Acclaim PLE+ is an ellipsoidal light designed specifically for larger theatrical spaces. The VL600 PLE+ is a 305W LED fixture with a multichromatic RGBL light engine that offers excellent key lighting for schools, theatres, and houses of worship, with over 15,000 lumens of output. The VL600 Acclaim PLE+ works with Vari-Lite's wide range of fixed and zoom lens tubes, ensuring there is a lens for any application. With the onboard four-blade manual shutter system, the VL600 PLE+ offers superior control to shape the light how you want it. Thanks to the optional size B metal gobo holder, designers can project depth and texture on stage, using the angle adjustment and manual focus to get the look just right. For applications where a low trim height is a challenge, the adjustable yoke allows the fixture to be positioned closer to the suspension point to give more headroom. Thanks to onboard Ethercon connectivity, the VL600 Acclaim PLE+ can be controlled directly via sACN or Art-Net without a separate DMX gateway. The VL600 PLE+ is sold in black or white.



- Multichromatic Light engine RGBL
- 305w Max Wattage
- 15,500 lm Max Lumen output
- Lockable continuous rotating gate and shutter assembly
- Dual B size gobo/iris slot

- Standard Vari-Lite lens tube configuration
- Height adjustable yoke
- Active fan controls and preset modes

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/acclaim-led-ple-plus>



VARI*RITE

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Source

LED	Multichromatic Light Engine - RGBL
Source Max Power Consumption	305 W
LED Refresh Rate	500 Hz to 4000 Hz
Dimming	Electronic 8-bit / 16-bit
Dimmer Curves	Square Law (Default), Linear, S -Curve
Strobe Speed	0 - 30Hz

Optical Performance

Output Lumens	Engine only - 15,500
CRI RA	7100 K - 85 5600 K - 84 3200 K - 84
Tm30	7100 K - Rf 77 / Rg 102 5600 K - Rf 78 / Rg 109 3200 K - Rf 78 / Rg 109
CQS	7100 K - 92
TLCI	7100 K - 73 5600 K - 73 3200 K - 70

Color System

Color Mixing	RGBL
Color Mixing Control	Open Source
Color Calibration	Selectable On/Off
Color Presets	40

Imaging

Shutter	4 blade manual framing shutters, locking rotating gate
---------	--

Electrical

Max output Power Consumption	310 W
Power Connection	TrueOne Compatible - In / Thru Power cable not included - input connector only
Input Voltage	100-240 VAC, 50 / 60 Hz
Standby Power	8.8 W

Data

Supported Protocols	DMX512-A (RDM), ArtNet, sACN
DMX Modes	
16-Bit	14 Channels
8-Bit	9 Channels
Data Connections	5 - Pin XLR Input and Thru, Ethercon Input and Thru
Manual Preset Mode	Advanced Feature local control

Noise Level / Fan Control (Base Level 21 dB @ 1 m (3.3 ft))

Standard Mode	42.8 dB
Studio Mode	35.5 dB
Whisper Mode	33.2 dB
Silent Mode	0.0dB
Fan Mode	Continuous (On) / Auto Ramping
Fan Level Preset	Standard, Studio, Whisper
Cooling System Type	Hybrid sealed liquid and forced air system


Mounting

Yoke	Double clutch locking yoke >270° Swivel Yoke M12 (1/2") Centre hole
Fixture mounting/Hanging orientation	Hanging - Floor - Side
Secondary Safety Wire Point	1 x Safety point located on rear of fixture housing Safety Wire not included

Photometrics and IES Files

For IES files and photometric reports, please refer to the product page:
<https://www.vari-lite.com/global/products/acclaim-led-ple-plus>

Dimensions



PLT SERIES	ORDER CODE
PLT 10° lens tube black	64010-002
PLT 10° lens tube white	64010-102
PLT 14° lens tube black	64010-003
PLT 14° lens tube white	64010-103
PLT 19° lens tube black	64010-004
PLT 19° lens tube white	64010-104
PLT 26° lens tube black	64010-005
PLT 26° lens tube white	64010-105
PLT 36° lens tube black	64010-006
PLT 36° lens tube white	64010-106
PLT 5° lens tube black	64010-001
PLT 5° lens tube white	64010-101
PLT 50° lens tube black	64010-007
PLT 50° lens tube white	64010-107
PLT 70° lens tube black	64010-008
PLT 70° lens tube white	64010-108
SPX ZOOM SERIES	ORDER CODE
25°-50° zoomspot lens tube black	SPX2550LT
15°-35° zoomspot lens tube black	SPX1535LT
SPX FIXED	ORDER CODE
14° fixed beam lens tube black	SPX14LT
19° fixed beam lens tube black	SPX19LT
26° fixed beam lens tube black	SPX26LT
36° fixed beam lens tube black	SPX36LT
50° fixed beam lens tube black	SPX50LT
LENS HOLDERS/ADAPTERS/GEL FRAMES	ORDER CODE
PLT FIXED LENS, 4 - Lug lens tube adapter, for use with ACCLAIM PLE, and LEKO LED Light sources, Black	64010-012
PLT FIXED LENS, 4 - Lug lens tube adapter, for use with ACCLAIM PLE, and LEKO LED Light sources, White	64010-112
Universal tube adapter black	PLPF4ULTA
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 5° Black	64010-909
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 10°, 14°, 19°, 26° Black	64010-910
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 36°, 50°, 70° Black	64010-911

Physical

Construction	Superstructure made of Aluminum, and steel metal plates, Covers self-extinguishing fire retardant ABS PC (V0 class)
IP Rating	IP20
Standard Finish	Black, White
Fixture Weight	8.1 kg (17.9 lb)
Packed Weight	10.2 kg (22.3 lb)
Operating Temperature	-10-40°C (14-104°F)

Certification and Safety

Approbations
 ETL (UL & CSA)CB/IECEE Scheme for CE-LVD, FCC, ICES, RCM, CE-EMC, UKCA, RoHS, ISO 9001

Gobo and Effect Wheels

Gobo Gate	B size (holder optional accessory)
Gobo Size	B

Luminaire and Accessories

Product type	Order Code
VL600 ACCLAIM PLE+, Black	64511-008
VL600 ACCLAIM LED PLE+, 305W Multichromatic Light Engine - RRGBL, c/w Power input connector, Black	
VL600 ACCLAIM PLE+, White	64511-108
VL600 ACCLAIM LED PLE+, 305W Multichromatic Light Engine - RRGBL, c/w Power input connector, White	

Accessories	
VL600 Acclaim B Size gobo holder	64511-012
VL600 ACCLAIM ZOOMSPOT/PLE, B Size Adjustable Gobo Holder - Metal or Glass images ,	
VL600 Acclaim IRIS	64511-013
VL600 ACCLAIM ZOOMSPOT/PLE, Iris	



© 2025 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Vari-Lite
<https://www.vari-lite.com/global/products/acclaim-led-ple-plus>