

VL600 ACCLAIM CYC

Date: _____

Type: _____

Firm Name: _____

Project: _____

The VL600 Acclaim Cyc luminaire delivers smooth even cyclorama lighting in a compact lightweight design. Using just 145 watts of power to illuminate drops up to 5 meters high, each unit can replace the equivalent of a traditional 4 color 500-watt luminaire. With true asymmetrical patented reflector technology and an RGBL color mixing system, The VL600 Acclaim Cyc offers homogenized, fully mixed color light output across a wide area with no multiple color shadows. The VL600 Acclaim Cyc Luminaire offers a simple spacing system and multiple mounting options, and it may be used for top or bottom lighting with units spaced on 1.2 meter (4ft) from the cyclorama @ 1.4 meter (4.5ft) centers for optimum performance and value.



- 500W/650W-equivalent LED cyclorama – cost-effective cyc luminaire
- Patented asymmetric reflector – a smooth even field for cycloramas up to 5m / 16ft high
- Simple spacing system – 1.2m - 4ft from cyc surface 1.4m / 4.5ft on center spacing
- Multiple mounting options – Designed for top or floor mounting with kick stand yoke

- Custom LED light source and RGBL color mixing system – Homogenized fully mixed color output light, no multiple color shadows. Consistent output and color mixing with the entire VL600 Acclaim Series
- Multiple fan/noise control modes and options – Get the perfect balance of output and sound for every moment.
- Available in black or white – the perfect body color for your application

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/acclaim-led-cyc>



VARI*LITE

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Source

LED	True RGBL LED engine, using custom designed LED array
Source Max Power Consumption	140 W
LED Refresh Rate	500Hz to 4000Hz
Dimming	Electronic 16-bit
Dimmer Curves	Square Law (Default), Linear, S -Curve
Strobe Speed	0 - 30Hz

Optical Performance

Beam Angle	42° Vertical / 38° Horizontal
Output Lumens	5800
CRI RA	7100 K - 82 5600 K - 86 3200 K - 83
TM30	7100 K - Rf 78 / Rg 98 5600 K - Rf 80 / Rg 107 3200 K - Rf 83 / Rg112
CQS	7100 K - 81 5600 K - 83 3200 K - 88
TLCI	7100 K - 76 5600 K - 77.6 3200 K - 77.3

Color System

Color Mixing	RGBL
Color Mixing Control	Open Source
Color Calibration	Selectable On/Off

Electrical

Output Power	145 W
Consumption	
Power Connection	TrueOne Compatible - In / Thru 762mm (30") Link Tails Built in Power cable not included - input connector only
Input Voltage	100-240 VAC, 50 / 60 Hz
Standby Power	10W

Data

Supported Protocols	DMX512-A (RDM)
DMX Modes	
16-Bit	11 Channels
8-Bit	8 Channels
Data Connections	5 - Pin XLR Input and Thru
Manual Preset Mode	Advanced Feature local control

Noise Level / Fan Control (Base Level 21 dB @ 1 m (3.3 ft))

Standard Mode	44.3 dB
Studio Mode	37 dB
Whisper Mode	33.2 dB
Fan Mode	Continuous (On) / Auto Ramping
Fan Level Preset	Standard, Studio, Whisper
Cooling System Type	Forced Air Cooling





Mounting

Yoke	Double clutch locking yoke >270° Swivel Yoke M12 (1/2") Centre hole
Rigging Orientation	Top or Bottom
Distance from Cyc	1.0 mm (5.0 in)
Fixture mounting/Hanging orientation	Top or Base of Cyc
Secondary Safety Wire Point	1 x Safety point located on rear of fixture housing Safety Wire not included

Photometrics and IES Files

For IES files and photometric reports, please refer to the product page:
<https://www.vari-lite.com/global/products/acclaim-led-cyc>

Dimensions



Physical

Construction	Machined aluminum, sheet metal, and molded engineering grade plastic components
IP Rating	IP20
Standard Finish	Black, White
Dimensions (w/ yoke)	239 x 241 x 277 mm (9.0 x 10.0 x 11.0 in)
Fixture Weight	5.0 kg (10.0 lb)
Operating Temperature	-10 - 40°C (14-104°F)

Certification and Safety

Approbations	ETL (UL & CSA)CB/IECEE Scheme for CE-LVD,FCC,ICES,RCM,CE-EMC,UKCA,RoHS, ISO 9001
--------------	--

Luminaire and Accessories

Product type	Order Code
VL600 ACCLAIM CYC, Black	64511-004
145W Multichromatic Light Engine - RGBL, c/w Power input connector, Black	
VL600 ACCLAIM CYC, White	64511-104
145W Multichromatic Light Engine - RGBL, c/w Power input connector, White	



© 2024 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

03/15/2024

Vari-Lite
<https://www.vari-lite.com/global/products/acclaim-led-cyc>