

Motif[™] risplendi. 250

250W, Full Color LED Pendant

RGBAL Color Mixing

Motif[™] Risplendi 250 is an ETL listed, full color architectural pendant light with a 250W RGBAL COB LED light source. It offers high CRI white and vivid mixed colors that can easily provide reading-level brightness when installed in high ceilings. It comes with four interchangeable lenses: 35°, 45°, and 60° Fresnel lenses, plus an 80° diffuser, for a variety of beam angles.

Versatile & Adaptable

Its stylish aluminum housing comes in your choice of black, white, or space gray, and its mounting options include an adjustable yoke or a stable bracket for permanent vertical installations. It offers switchable power that includes a powerCON TRUE1[™] compatible input and terminal block for hardwiring, plus it also has emergency power connections so you'll never be left in the dark.

Luminous Intensity

Lux/Meter	2.5 Meter	5 Meter	7.5 Meter
35° Lens	5,976	1,822	815
45° Lens	5,722	1,640	734
60° Lens	4,296	1,059	489
80° Lens	1,759	488	226



Housing colors:

- Black
- White
- Space Gray



Part# SNOOT-Motif Risplendi B,
W, or SG (not included).

Main Features

- Light source: 250W RGBAL COB LED
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Color mixing ability in standalone mode
- 4x light collimating lenses (35°, 45°, 60°, 80°)
- Convection cooled aluminum housing
- Dual mounting brackets for positioning flexibility
- Adjustable LED refresh rates (1200Hz-20KHz)
- PowerCON[®] TRUE1[™] compatible power input
- Hardwired AC power connections
- Power backup connector (42-48V DC, 20W)
- 5-pin XLR input & output connections
- 8.5 cm snoot, full shield attachment (sold separately)



Optical

250W RGBAL COB LED,
100,000 hrs.

4x interchangeable light
collimating lenses:

35°, 45°, 60°, 80°

PWM refresh rates:
1200Hz-20KHz



Weight & Dimensions

13.7" x 10.5" x 7.9" (347
x 266 x 200 mm)

15 lbs. (6.8 kg)



Control

USITT DMX-512, RDM

5-pin DMX in/out

5/7/11-channel DMX

4-button menu with
OLED display

DMX512, M/S, standalone,
auto mode



Power + Current

100-240VAC, 50-60 Hz

Consumption: 204W,
1.81A, PF: .98

PowerCON[™] TRUE1-
compatible input +
hardwire connections



Warranty + Certifications

7-year limited warranty

cETLus certified



www.blizzardpro.com

info@blizzardpro.com

1.866.493.6025



Like



Watch



Follow